



All-Purpose Foaming Cleaner

FEATURES

- Designed to remove grease and soil
- Clinging foam permits long lasting contact with surfaces to be cleaned
- Use to clean countertops, walls, cabinets, and greasy parts

APPLICATIONS

- Plastic
- Ceramic
- Concrete
- Metal
- Urethane
- and more

DIRECTIONS

Spray evenly over surface. Wipe clean or spray with clean water. For heavily soiled surfaces, have product remain on surface for an extended period of time.

HANDLING

Shake well before using. Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

STORAGE

Protect from sunlight. Store in a well-ventilated place. May explode if heated. KEEP OUT OF REACH OF CHILDREN.

DISPOSAL

Dispose of contents/container according to local/national disposal regulations.



PROPERTIES

Appearance / Physical State	Aerosol
Odor	Citrus
Vapor Pressure	60 psig @ 21°C (70°F)
Flammability	Not applicable
Propellant	Isobutane/propane blend
VOC Content	7.99%
Color	Colorless
Flash Point	N/A
Density	Not determined
Evaporation Rate	N/A
Vapor density	> 1 (Air=1)
Auto-Ignition Temperature	Product is not self-igniting
Viscosity	Not determined
Density	1.01 g/cm (8.428 lbs/gal) @ 20°C (68°F)
pH Value	9.8 - 11.0
Water Solubility	Soluble

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
19220	18 oz / 510 g	aerosol	12	18 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved