

Product Data Sheet

No. 1117 - 05/20

GLOSS CLEAR ACRYLIC COATING

AEROSOL CARB MIR ≤ 0.85

PRODUCT NUMBERS: 117 - 12 OZ. NET WT.

I. GENERAL DESCRIPTION

Description: Gloss Clear Acrylic is formulated to cover and seal with a lustrous, smooth finish. It is an excellent weatherproof coating that provides long-lasting protection against wear, handling, and oxidation.

Benefits: Will not fade or cause discoloration, tarnishing, bleaching, or fading from sunlight. It resists salts, alkalis, weak acids, heat and cold. This product will begin to soften at 150°F (66°C) but will regain hardness upon cooling.

Application: Use on brass fixtures, tubing, machine parts, whenever a protective film can be used to prevent oxidation. It will adhere to metals, wood, and paper.

Directions: Surfaces must be dry and free of dust, dirt, oil, grease, wax and other contaminants that would adversely affect paint adhesion. For best results product should be used when air and surface temperatures are between 60° and 80°F (16° and 27°C). Align spray head with black mark on valve rim to ensure complete evacuation. Before spraying, shake can vigorously for at least 1 minute after agitator ball is heard and intermittently thereafter. Hold can 12 to 14 inches from surface to be coated, and press spray head firmly. Use steady, even strokes while spraying, making sure to keep spraying hand in motion. Two light coats are better than one heavy coat. Spray in well ventilated area. After spraying, turn can upside down and press button for approximately two seconds to clear paint in valve.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc. Do not apply if air or surface temperatures are below 50°F (10°C) or rain is imminent within 6 hours. **NOT AN AUTOMOBILE FINISH. DO NOT APPLY TO ENERGIZED EQUIPMENT.**

Packaging:

Aerosol:	Cans (16 oz.)	12 oz. net wt. (340 grams)	13.6 fl. oz. (402 ml)
	12 cans/case	14 lbs. (6.4 kg)	0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES

Specifications:

None

Appearance:

Gloss at 60°>90

Class Clear Coating

Coverage:

Theoretical (at 1 mil dry) 14.7 sq. ft./can

Practical (at 1/2 mil dry) 29.4 sq. ft./can

Drying Schedule (at 77° F [25° C], 50% Humidity at 1 mil dry):

To touch..... 5 min

To handle..... 10 min.

To recoat Anytime

Full cure 24 hrs

Performance and Chemical Properties:

Weight per gallon 6.14 lbs./gal

Specific gravity 0.7

Viscosity Not Applicable

Flammability: Label marking Extremely Flammable

Flash point..... <0°F (-18°C)

Operating temperature range 50° to 90°F (10° to 32°C)

Percent solids by weight 10.6%

Percent solids by volume 7.5%

CARB MIR (Clear Coating) ≤0.85

Interior durability..... Excellent

Exterior durability Excellent

Temperature resistance..... Softens at 150°F (66°C)

Adhesion (ASTM D3359) Good

Mineral Spirits resistance Excellent

Gasoline resistance..... Poor

Motor Oil resistance Good

Pencil hardness (ASTM D3363)..... HB

Base Materials:

Resin system..... Acrylic

Solvents (top two) Acetone, n-Butyl Acetate

Propellant..... Hydrocarbon

III. SHIPPING, STORAGE AND HEALTH

UN number..... UN1950

Proper Shipping Description Aerosols

Hazard Class..... 2.1

Packing Group N/A

Limited Quantity Yes

Warehouse storage level number NFPA 30B Level 2

Storage temperature 32° to 120°F (0° to 49°C)

Shelf life 1 to 2 years

HMIS ratings

Health 2

Fire 4

Reactivity..... 1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year performance warranty on all products from date of purchase. Report to home office or local Aervoe representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.