

Product Data Sheet

No. 1214 - 07/17

MARKING CHALK

GROUND TRAFFIC/MARKING COATINGS: AEROSOL VOC ≤66%; CARB MIR ≤0.85

PRODUCT NUMBERS:

214 - BLUE 217 ORANGE
215 WHITE 218 YELLOW
216 RED 219 GREEN

I. GENERAL DESCRIPTION

Features: A unique, temporary, water-based marking chalk. This product is safe for use at all construction, utility, and survey sites. Aervoe Water-Based Marking Chalk is packaged to operate upside down by hand or in an Aervoe Spot Marker #244, or Marking Stick #245 applicator, with or without the cap on.

Benefits: This product is a true water-based formula, not "water added" for cost reduction formula. Adhesion is provided by non-resin binders and low pigment solids in a slurry that holds the chalk together as the mark dries. It is a fast-drying chalk designed for **temporary** marking. The mark will naturally disappear with water, traffic, or other abrasions.

Uses: Aervoe Marking Chalk is designed to temporarily mark most paved surfaces, soil, and grass. Use for utility marking, construction sites, surveying, landscaping, and athletic field marking. For golf course marking, use Aervoe Water-Based Marking Paint. For aisle striping in warehouses, parking lots, or traffic lines, use Aervoe Striping Paint.

Application: For aerosol application, shake can for 1 to 2 minutes after rattle of the agitator ball is heard. Remove safety tab, invert can, and apply 3 to 4 inches from the surface for writing symbols and numbers. Apply 5 to 8 inches from the surface for 3/4" line or continuous direction tracks. Product will appear transparent when first applied; full opacity is achieved in 3 to 5 minutes. Keep can in motion during use to prevent puddling due to high delivery paint stream. For best results, use at temperatures between 50° and 80°F (10° and 27°C). If cap has been removed, replace it for storage and color identification. Clear spray tip after each use by turning can upright and spraying for 2 to 3 seconds.

Limitations: Please refer to the Safety Data Sheets for specific information on material hazards, etc. This aerosol product is designed to spray **upside down** or at an angle not greater than 30° from vertical. Please check your local air quality standards before using any bulk paint. Use caution if surface is wet, or if rain is imminent within 4 hours of application. Do not apply additional product until the previous coat is dry. On fresh asphalt or other porous surfaces, removal may be hampered due to solvent/pigment penetration.

Packaging:

Aerosol:	Cans (20 oz.)	15 oz. net wt. (425 g)	14.8fl. oz. (437 mL)
	Case - 12 cans/case	16 lbs. (7.3k g)	0.55 CF (0.016 CM)

II. CHARACTERISTICS & PROPERTIES

Average for all colors

Specifications: Colors formulated to approximate standards set by OSHA and APWA/One Call systems. These products meet the CARB MIR regulations.

Appearance:

Gloss at 60° <math><5\%</math>

Class Flat

Coverage:

Aerosol

Theoretical—at 1 mil dry 464 linear ft./can

Practical—at 1/2 mil dry 928 linear ft./can

Drying Schedule: (At 77°F [25°C], 50% Humidity at 1 mil, dry)

To touch 8 min.

To handle 15 min.

Full cure 8 hrs.

To recoat Not required

Performance and Chemical Properties:

Weight per gallon 8.13 lbs.

Specific gravity 0.98

Viscosity Not applicable

Flammability: Label marking Not applicable

Flash point Not applicable

Operating temperature range 50° to 80°F (10° to 27°C)

Percent solids by weight 27%

Percent solids by volume 16%

Percent pigment by volume 7%

Volatile Organic Compound level <math><66\%</math>

CARB MIR ≤ 0.85

Interior durability Poor

Exterior durability Poor

Temperature resistance Not applicable

Color fastness Fair

Adhesion Poor

Salt spray corrosion Not applicable

Mineral spirits resistance Poor

Gasoline resistance Poor

Motor oil resistance Poor

Pencil hardness Not applicable

Base Materials

Resin system None

Solvents (top two) Water/Alcohol

Propellant system Dimethyl Ether

III. SHIPPING, STORAGE AND HEALTH

UN number UN1950

Proper Shipping Description Aerosols

Hazard Class 2.1

Packing Group N/A

Limited Quantity Yes

Warehouse storage level number NFPA 30B Level 2

Storage temperature 32° to 120°F (0° to 49°C)

Shelf life 1 to 2 years

HMIS ratings

Health 1

Fire 2

Reactivity 1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.