HIGH HEATTM Product # 616

Granular drain opener

This drain opener contains powerful caustic granules activated with aluminum needles to quickly unclog drains and sewers and keep them free-flowing. When added to water, it releases large amounts of heat and turbulence to liquefy, dissolve and loosen fats, oils and other organic matter that typically clog drains and sewer lines. Even though it's extremely powerful, it will not harm drains, pipes and septic systems.

Use in:

Manholes
 Drains
 Food plants
 Packing houses
 Canneries

Effective Against

- Animal fatsHairVegetable oilsPaper
- Organic matter

 Hard-water soap deposits

Features and Benefits

- Contains powerful heat-generating aluminum needles.
- Releases large amounts of heat and turbulence to liquefy blockages in drains and sewers.
- Loosens and dissolves grease and other organic material.

Properties	
Appearance	Yellow pellets with aluminum granules
Fragrance	None
Flash point	None
pH	14.0
Stability	1 year
Solubility in water	Complete (very reactive)

Directions Complete directions on product label

Floor Drains: Carefully pour 3 scoops into drain. Add 3 cups of cold water to the drain immediately. If water boils out of drain, immediately add another cup of COLD water.

Small Drains: Follow the above procedure, but decrease the dosage to 1 scoop and immediately add 1 cup of cold water.

Authorizations

NSF L1: Compounds for use in sewage and/or drain lines.

Ingredients	CAS Number
Sodium Hydroxide	1310-73-2
Sodium Nitrate	7631-99-4
Sodium Chloride	7647-14-5
Aluminum metal	7429-90-5
Dye	Mixture

Safety

DANGER: May intensify fire; oxidizer. Causes severe skin burns and eye damage. May cause respiratory irritation.

DOT Shipping (ground transportation)

Proper Shipping Name: Corrosive solid, basic, inorganic, n.o.s.

(Sodium Hydroxide)

Class: 8

ID Number: UN3262 Packing Group: II

NFPA® RATINGS Flammability Health Reactivity

Quantities

55 pound pail 6x2 pound jars

