

KICK OFF

SAFETY SOLVENT



DESCRIPTION

KICK OFF is a high powered, non-flammable, non-conductive solvent that dissolves grease and rinses away dirt and grime from hard surfaces without injury to working parts. Contains an acceptable replacement for 1,1,1 trichloroethane under the EPA SNAP program. Contains no CFC's. Featuring a 30,000 volt dielectric strength combined with non-flammability makes this an exceptional degreaser safe for use on electric motors, generators, relays and control panels while equipment is in operation. Dries fast and residue free. No flash point. Cleaning is quick and simple with the powerful flushing action of the solvent without the danger of injury to working parts.

APPLICATIONS

Excellent for use on electric motors, bearings, gears, gas, water and electric meters, pipe threads, machined parts. For use by downhole tool companies, wireline companies, electrical pump companies, machine shops, oilfield services companies, pipe yards.

FEATURES & BENEFITS

- Non-Flammable & Non-Conductive
- 30,000 Volt Dielectric Strength
- Non-Corrosive
- Fast Drying & Residue Free

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 200 ppm
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: N/A
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.52
% VOC: 96%
pH: N/A
VISCOSITY: Thin
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

KICK OFF SAFETY SOLVENT

KICK OFF is a high powered, non-flammable, non-conductive solvent that dissolves grease and rinses away dirt and grime from hard surfaces without injury to working parts. Contains an acceptable replacement for 1,1,1 trichloroethane under the EPA SNAP program. Contains no CFC's. Featuring a 30,000 volt dielectric strength combined with non-flammability makes this an exceptional degreaser safe for use on electric motors, generators, relays and control panels while equipment is in operation. Dries fast and residue free. No flash point. Cleaning is quick and simple with the powerful flushing action of the solvent without the danger of injury to working parts.

DIRECTIONS: Spray liberally over grease and grime until completely saturated. Allow the solvent to air dry. For extreme cleaning, brush encrusted part and rinse again with solvent spray. Parts should dry rapidly with a residue free surface.

DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause cancer. May cause drowsiness or dizziness. Suspected of causing genetic defects.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, eye protection, and protective clothing. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

WARNING: This product can expose you to chemicals including Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

INGREDIENTS (CAS#): Trichloroethylene (79-01-6), Carbon Dioxide (124-38-9).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 20 oz. cans per case, 19 oz. net weight.