

PIERCE

PENETRATING LUBRICANT



DESCRIPTION

PIERCE is a USDA authorized lubricating product. Formulated to quickly penetrate rust, corrosion and moisture. Lubricates, cleans and contains rust preventative. Non-flammable and non-conductive to 30,000 volts. Four-way action cleans, lubricates, prevents rust and penetrates. Due to VOC regulations, not available for sale in California.

APPLICATIONS

For use on motors, wire cable, rusted parts, ignition systems, machine parts, door hinges, locks, nuts and bolts and refrigeration equipment. Areas of use include homes, hotels/motels, airplanes, cars and trucks, machine shops, oil rigs, manufacturing facilities, industrial plants and factories.

FEATURES & BENEFITS

- Versatile light duty formula penetrates, lubricates, prevents corrosion and displaces moisture
- Silicone free formula will not interfere with subsequent painting
- Non-flammable
- Meets MIL Spec C-23411

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 100 ppm OSHA PEL TWA
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.52
% VOLATILE BY VOLUME: 100%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Medium
BIODEGRADABILITY: No

LABEL INFORMATION

PIERCE PENETRATING LUBRICANT

PIERCE penetrating lubricant is a non-flammable powerful, multiple-action penetrant and protective shield. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.

SUGGESTED USES

- Start Wet Engines
- Freeing Nuts & Bolts
- Electrical Panel Board
- Vending Machines
- Remove Moisture from Ignition Wires
- Stops Corrosion on Battery Terminals
- Airplanes
- Parking Meters
- Refrigeration Equipment
- Laundromats

DIRECTIONS: Spray liberally directly on area to be treated. Reapply periodically as required.

DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. May cause cancer. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly

after handling. Wear protective gloves, eye protection, and protective clothing. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

Warning: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Petroleum Distillate (64741-44-2), Carbon Dioxide (124-38-9), Sorbitan Monooleate (1338-43-8), Methyl Salicylate (119-36-8).

Made in USA

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

5090: 12 – 20 oz. cans per case, 18 oz. net weight (Private Label Only)
 5500: 12 – 16 oz. cans per case, 16 oz. net weight