

# MISTER BLISTER

## METHYLENE CHLORIDE FREE PAINT REMOVER



### DESCRIPTION

**MISTER BLISTER** is a gel-based paint remover. The methylene chloride free formula is a safer alternative to paint removal. Penetrates deep to remove paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials from all surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces.

### APPLICATIONS

Works hard to remove paint, lacquer, carbon deposits and silicone. Areas of use include auto dealers, paint shops, factories, schools, farms, oil rigs, bottling plants, lumber mills and cement plants.

### FEATURES & BENEFITS

- Gel-based formula clings to vertical surfaces, allowing longer contact time
- Removes a wide range of paints and surface sealers from metal, concrete and wood
- Ease of use—simply spray on and wipe or rinse

### SPECIFICATIONS

**FORM:** Solvent-Based Aerosol  
**ODOR:** Acetone  
**COLOR:** Blue-Green  
**DETERGENCY:** Strong  
**TOXICITY:** 1000 ppm  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**% VOC's:** 49.5%

**FLASH POINT:** N/A  
**FLAME EXTENSION:** None  
**SOLUBILITY IN WATER:** 100%  
**SPECIFIC GRAVITY:** 0.95-0.98  
**% VOLATILE BY VOLUME:** 81.5%  
**pH:** N/A  
**PROPELLANT:** Hydrocarbon  
**VISCOSITY:** 100-300 cps  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### MISTER BLISTER METHYLENE CHLORIDE FREE PAINT REMOVER

Gel formulation paint remover quickly removes paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run.

**FOR USE BY:** Auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices.

**FOR USE ON:** Metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry & cylinders.


**DIRECTIONS:** Shake well before using. Holding can 8-10 inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

**DANGER:** Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin irritation and serious eye damage. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well ventilated place. Wash hands with soap and water thoroughly after handling. Wear protective gloves/eye protection/face protection. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Use only outdoors or in a well ventilated area. Call a poison center/doctor if you feel unwell. Do not eat, drink, or smoke when using this product. Get medical advice/attention if you feel unwell. Dispose of contents/container in accordance with local, state, and federal law.

**CONTAINS (CAS#):** Dioxolane (646-06-0), Acetone (67-64-1), Propane/n-Butane (68476-86-8), Dimethyl Carbonate (616-38-6), Isopropylidene Glycol (100-79-8).

HEALTH	3
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

12 – 16 oz. cans per case, 11 oz. net weight