

CLINCH

BATTERY PROTECTANT



DESCRIPTION

CLINCH is a light misting, purple coating designed to prevent rust, corrosion and battery failure. Provides a long-term protection when applied to battery terminals, cable ends, wires, bolts, brackets, clamps and other metal components. One application is effective for up to 6 months. Proper use keeps batteries clean, prolongs life and helps prevent terminal contact failures. Every new battery installation and service should be completed with an application of CLINCH. Also, great for rust prevention on a variety of other metal surfaces. The distinctive color shows where protection is working. Use on all batteries whether in or out of storage.

APPLICATIONS

For use on automotive batteries, cables, construction equipment, forklifts, golf carts, electrical connectors, trucks, marine equipment, boats, lawn mowers and other metal surfaces.

FEATURES & BENEFITS

- Leaves a purple visible protective coating
- Prolongs life of battery and related components—helps eliminate battery failure
- Use on many other metal surfaces to prevent rust and corrosion

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Strong Solvent
COLOR: Red
DETERGENCY: None
TOXICITY: 300 ppm
WETTING ABILITY: N/A
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
SPRAY PATTERN: Fine Mist

FLASH POINT: Not Tested
FLAME EXTENSION: 18"
SOLUBILITY IN WATER: None
SPECIFIC GRAVITY: 0.76
% VOLATILE BY VOLUME: 61%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

CLINCH BATTERY PROTECTANT

CLINCH is a light misting, purple coating designed to prevent rust, corrosion and battery failure. Provides a long-term protection when applied to battery terminals, cable ends, wires, bolts, brackets, clamps and other metal components. One application is effective for up to 6 months. Proper use keeps batteries clean, prolongs life and helps prevent terminal contact failures. Every new battery installation and service should be completed with an application of CLINCH. Also, great for rust prevention on a variety of other metal surfaces. The distinctive color shows where protection is working. Use on all batteries whether in or out of storage.


DIRECTIONS: Be sure ignition is off before spraying. Do not apply near hot surfaces. Shake can well before using. Remove cables from battery terminals. Clean all surfaces with DETECT Battery Cleaner & Acid Detector. Protect against overspray by covering surrounding areas. Spray terminals with light coating. Replace and tighten cables. Coat metal surfaces with a generous amount from 8-12" away. Wait 5 minutes before starting engine.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May cause damage to organs through prolonged or repeated exposure. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Do not breathe fumes, mist, vapors, and spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Get medical attention if you feel unwell. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Aliphatic Petroleum Distillate (64742-89-8), Heptane (142-82-5), Propane/n-Butane (68476-86-8).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz. cans per case, 12 oz. net weight