

DETECT

BATTERY TERMINAL CLEANER



DESCRIPTION

DETECT cleans and neutralizes acid on terminals and cables of batteries. A color indicator is provided with the product to detect acid leaks. Product turns red on contact with battery acid. Battery terminal cleaner eliminates corrosion buildup, prolonging battery life and effectiveness.

APPLICATIONS

For use on car batteries, cables, construction equipment, forklifts, golf carts, electrical connectors, batteries, trucks, marine equipment, boats and lawn mowers.

FEATURES & BENEFITS

- Quickly cleans away dirt and grease—prolongs battery life
- Contains red color indicator to detect leaks
- Easy to use. Simply spray on and wipe off. Severe corrosion may require light brushing.

SPECIFICATIONS

FORM: Water-Based Aerosol Foam
ODOR: Mild Ammonia
COLOR: Orange
DETERGENCY: Excellent
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 0
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 1.00
% VOLATILE BY VOLUME: >80%
pH: 10.8
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

DETECT BATTERY TERMINAL CLEANER


This product is designed to clean and protect batteries. A color indicator is included to assist in detecting leaks. Battery terminal cleaner eliminates corrosion buildup and provides a residual corrosion preventive. This product is ideally suited to use on batteries in fleet cars, trucks, buses, golf carts, fork trucks, construction and agricultural equipment.

DIRECTIONS: Shake well before using. Spray on cables, clamp terminals, brackets and over entire battery surface. Be sure cell covers are tightly closed prior to spraying. After a few minutes, flush off with water or damp cloth. Formula is yellow but turns red in presence of acid. Spray will neutralize any acid on battery.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

CONTAINS (CAS#): Water (7732-18-5), Propane/n-Butane (68476-86-8), Isopropyl Alcohol (67-63-0), 2-Butoxyethanol (111-76-2).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

12 – 20 oz. cans per case, 18 oz. net weight