

FUEL GUARD

DIESEL FUEL STABILIZER

DESCRIPTION

FUEL GUARD is an unparalleled fuel conditioner that responds to an entirely new set of demands created by new low sulfur fuels, as well as satisfying the needs of previous fuel related problems. FUEL GUARD not only helps to stabilize the fuel, but also increases engine life and power, by keeping the internal parts of the engine cleaner, aiding combustion, neutralizing acids and holding carbon, varnish and gum in suspension. This suppresses the tendencies of icing and corrosion.

APPLICATIONS

Trucking, heavy construction, agriculture, mining equipment, industrial equipment, marine and fuel storage.

FEATURES & BENEFITS

- Prevents slime build-up
- Reduces fuel consumption
- Neutralizes harmful engine acids
- Provides lubricity for low sulfur fuel
- Keeps injections running clear
- Prolongs pump and injector life
- Increases horsepower output

SPECIFICATIONS

<p>FORM: Solvent-Based Liquid ODOR: Slight Petroleum COLOR: Clear Amber STORAGE STABILITY: 1 Year +</p>	<p>FLASH POINT: >212°F POUR POINT: -51°F SPECIFIC GRAVITY: .87 VISCOSITY @ 40°F) >5.3 CST EVAPORATION RATE: Slow</p>
--	---

LABEL INFORMATION

FUEL GUARD DIESEL FUEL STABILIZER

FUEL GUARD is an unparalleled fuel conditioner that responds to an entirely new set of demands created by new low sulfur fuels, as well as satisfying the needs of previous fuel related problems. FUEL GUARD not only helps to stabilize the fuel, but also increases engine life and power, by keeping the internal parts of the engine cleaner, aiding combustion, neutralizing acids and holding carbon, varnish and gum in suspension. This suppresses the tendencies of icing and corrosion.

RECOMMENDED TREAT RATE:

UNTREATED ENGINES: 1 quart per 50 gallons of fuel. CONTINUED TREATMENT: 1 quart per 200 gallons of fuel. STORAGE TANK TREATMENT: 1 gallon per 2000 gallons of fuel or 1 quart per 500 gallons.

CAUTION: COMBUSTIBLE. Keep away from heat and open flames. Contains petroleum distillates. Do not take internally. Avoid contact with eyes. In case of contact, immediately flush eyes with water for 15 minutes. If irritation persists, see physician. If swallowed, see physician immediately.

Contains (CAS#): Petroleum Distillate Mixture (N/A), Additive (N/A).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

Available in 12 x 1 quarts, 5 gallon pails and 55 gallon drums.