

Safety Data Sheet
No Mischief

SECTION I - IDENTIFICATION

PRODUCT NAME: No Mischief
PRODUCT CODE: 2150
PRODUCT USE: Mark Resistor
COMPANY NAME: QuestSpecialty Corporation
COMPANY ADDRESS: P.O. Box 624 Brenham, TX 77834
COMPANY PHONE: 800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Liquefied Gas

Skin Irritant: Category 2

Eye Irritant: Category 2A

Reproductive Toxicity: 2

Specific Target Organ Toxicity (Single Exposure): Category 3

Specific Target Organ Toxicity (Repeated Exposure): Category 1

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause respiratory irritation, drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 18%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eyewear. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Do not eat, drink or smoke when using this product. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Propane/n-Butane	68476-86-8	10-30%
Hexane	110-54-3	30-60%
Heptane	142-82-5	10-30%
Light Aliphatic Solvent Naphtha	64742-89-8	7-13%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Safety Data Sheet

No Mischief

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

CHRONIC HEALTH HAZARDS: Excessive exposure may result in peripheral neuropathies due to n-hexane. Symptoms would be sensory numbness and possible motor weakness in extremities.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, various hydrocarbons

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.

WASTE DISPOSAL: Dispose of in accordance with local, State and Federal regulations. Do not dump in sewers. Use sand or other non-combustible absorbent material to clean up spill and place in container for later disposal. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Strong acids, strong oxidizing agents (chlorine and other halogens, chromates, perchlorates and oxygen.)

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Propane/n-Butane	1000 ppm	1000 ppm
Hexane	500 ppm	500 ppm
Heptane	500 ppm	400 ppm
Light Aliphatic Solvent Naphtha	300 ppm	300 ppm

ENGINEERING CONTROLS / VENTILATION: Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

RESPIRATORY PROTECTION: If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Colorless Spray

Safety Data Sheet

No Mischief

ODOR: Solvent odor
ODOR THRESHOLD: N/D
BOILING POINT: N/D
FREEZING POINT: N/D
FLAMMABILITY: Extremely Flammable Aerosol
FLASH POINT: N/D
AUTOIGNITION TEMPERATURE: N/D
LOWER FLAMMABILITY LIMIT: N/D
UPPER FLAMMABILITY LIMIT: N/D
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): > 2
EVAPORATION RATE: Fast
SPECIFIC GRAVITY (H₂O=1): 0.690 @ 77° F (25° C)
pH: N/A
SOLUBILITY IN WATER: 0%
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
VOLATILE ORGANIC COMPOUNDS (VOC): 97%
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: None Known
CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.
INCOMPATIBILITY: Strong acids, strong oxidizing agents (chlorine and other halogens, chromates, perchlorates and oxygen.)
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of Carbon, and other Decomposition products.
POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Hexane (110-54-3) LD₅₀ (Oral, Rat) > 5000 mg/kg; LD₅₀ (Dermal, Rabbit) > 2000 mg/kg;
LC₅₀ (Inhalation, Rat, 4hrs) > 3367 ppm
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: May cause burning, irritation, redness, tearing
INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting, aspiration hazard.
INHALATION: May cause irritation to the respiratory tract, dizziness, headaches, drowsiness, unconsciousness.
SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.
MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.
ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision
Skin: defatting and dermatitis
Inhalation: Anesthetic, irritation, Central Nervous System depression
Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk
CHRONIC HEALTH HAZARDS: Excessive exposure may result in peripheral neuropathies due to n-hexane. Symptoms would be sensory numbness and possible motor weakness in extremities.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not Established
BIODEGRADABILITY: This product is biodegradable.
BIOACCUMULATION: This product is not expected to bioaccumulate.
SOIL MOBILITY: This product is mobile in soil.
OTHER ECOLOGICAL HAZARDS: This material is toxic to aquatic life.

Safety Data Sheet
No Mischief

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, State and Federal regulations. Do not dump in sewers. Use sand or other non-combustible absorbent material to clean up spill and place in container for later disposal. Do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: Acute Health, Chronic Health, Fire Hazard

SARA 313 REPORTABLE INGREDIENTS: n-Hexane (110-54-3)

STATE REGULATIONS: CA Prop 65: This product can expose you to chemicals including n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm.

INTERNATIONAL REGULATIONS: All components of this product are on the Canadian DSL list.

NFPA HEALTH: 2

HMIS HEALTH: 2

NFPA FLAMMABILITY: 3

HMIS FLAMMABILITY: 3

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: None

HMIS PROTECTION: B

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Chioma Agbai

DATE PREPARED: 08/15/2014

REVISION DATE: 03/16/2018

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the

Safety Data Sheet

No Mischief

manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.