

# SAFE BET

## PENETRATING GREASE

### DESCRIPTION

**SAFE BET** is a multi-purpose lithium complex lubricant, penetrant and rust preventative that changes from a fluid to become a tough, protective grease in minutes. Ideal for hard to reach areas on all door hardware and operator drive mechanisms. Once grease has set up it will outlast any regular oil or silicone. 50 state VOC compliant.

### APPLICATIONS

For use on machinery, conveyors, chains, cables, gears, winches, tools, rollers, springs, hinges, operators and rollers. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

### FEATURES & BENEFITS

- Lithium complex formula
- Lubricant, penetrant & rust preventative
- 50 state VOC compliant
- Methylene chloride free formula
- Sprays on like an oil & sets up to a tough grease in minutes
- Temperature range 0°F to 350°F

### SPECIFICATIONS

<p><b>FORM:</b> Solvent-Based Aerosol  <b>ODOR:</b> Solvent  <b>COLOR:</b> Amber  <b>DETERGENCY:</b> None  <b>TOXICITY:</b> 400 ppm  <b>WETTING ABILITY:</b> N/A  <b>STORAGE STABILITY:</b> 1 Year +  <b>COLD STABILITY:</b> 0°F  <b>PHOSPHATES:</b> None</p>	<p><b>FLASH POINT:</b> N/A  <b>FLAME EXTENSION:</b> N/A  <b>SOLUBILITY IN WATER:</b> N/A  <b>SPECIFIC GRAVITY:</b> 0.82  <b>% VOLATILE BY VOLUME:</b> &gt;50%  <b>pH:</b> N/A  <b>PROPELLANT:</b> Hydrocarbon  <b>EVAPORATION RATE:</b> N/A  <b>BIODEGRADABILITY:</b> No</p>
---	--

### LABEL INFORMATION

#### SAFE BET PENETRATING GREASE

SAFE BET is a multi-purpose lithium complex lubricant, penetrant and rust preventative that changes from a fluid to become a tough, protective grease in minutes. Ideal for hard to reach areas on all door hardware and operator drive mechanisms. Once grease has set up it will outlast any regular oil or silicone. Areas of use include machinery, conveyors, chains, cables, gears, winches, tools, rollers, springs, hinges, operators and rollers. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive, motorcycle, marine repair. 50 state VOC compliant.


**DIRECTIONS:** Spray a thin film on surfaces to be lubricated. For best results, spray in short bursts. Material will start forming grease in minutes. Allow 15 minutes for product to fully cure.

**DANGER:** Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

**INGREDIENTS (CAS#):** Severely Refined Mineral Oil (64742-52-5), Acetone (67-64-1), Petroleum Distillates, hydrotreated light (64742-47-8), Propane/n-Butane (68476-86-8), Heptane (142-82-5).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

12 – 20 oz. cans per case, 13.5 oz. net weight