

REVIVE

RUST CONVERTER SPRAY



DESCRIPTION

REVIVE is the quick and convenient way to treat rusted surfaces. This product chemically converts the rust to an inert black polymer based coating that prevents future rust from forming. Eliminates the need for brushing, sandblasting or scraping before painting rusted surfaces. Once treated, surface may be left unpainted or may be painted for improved appearance and protection. May be used on all rusted surfaces. Convenient spray can allows for quick, mess-free application. Combines a unique fast drying carrier with special rust converting agents and a strong polymeric coating. RUST CONVERTER: MIR: 1.1

APPLICATIONS

Areas of use include machinery, industrial equipment, marinas, tank yards, farm equipment, manufacturing plants, fencing, shipyards, metal buildings, tools, railroads and more.

FEATURES & BENEFITS

- Ease of use eliminates the need for sanding, brushing and scraping.
- Prevents rust from forming.
- Allows treated surface to be painted.

SPECIFICATIONS

FORM: Aerosol
ODOR: Solvent
COLOR: Clear Brown
DETERGENCY: None
TOXICITY: 25 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
% VOC: 44%

FLASH POINT: 65°F
FLAME EXTENSION: 18"
SOLUBILITY IN WATER: Non-soluble
SPECIFIC GRAVITY: 0.85
% VOLATILE BY VOLUME: 90%
pH: 1.9
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: No

LABEL INFORMATION

REVIVE RUST CONVERTER SPRAY

REVIVE Rust Converter Spray is the quick and convenient way to treat rusted surfaces. This product chemically converts the rust to an inert black polymer based coating that prevents future rust from forming. Eliminates the need for brushing, sandblasting or scraping before painting rusted surfaces. Once treated, surface may be left unpainted or may be painted for improved appearance and protection. May be used on all rusted surfaces. Convenient spray can allows for quick, mess-free application. Combines a unique fast drying carrier with special rust converting agents and a strong polymeric coating.

RUST CONVERTER: MIR: 1.1

DIRECTIONS FOR USE: For best results, remove loose particles of rust and debris using a wire brush or rag. Be sure surface to be treated is dry and free of water. Shake can for 30 seconds before application. Remove protective cap and point opening in spray tip towards surface to be treated. Using a slow sweeping motion and holding can 8–12 inches from surface apply a thin coat covering all of the rusted area. Allow to dry. The surface will turn black. Apply a second thin coat. Allow surface to dry for 48 hours to promote complete curing of the polymeric coating. For additional protection apply 1 or 2 coats of a suitable spray paint.

Apply the product when temperatures are between 50°F and 95°F. Store in a cool, dry area where temperatures are below 100°F.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation.

PACKAGING INFORMATION

12 – 20 oz. cans per case, 13 oz. net weight

May cause drowsiness or dizziness.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Acetone (67-64-1), Isopropanol (67-63-0), Diethylene Glycol (111-46-6), 2-Butoxy Ethanol (111-76-2), Tannic Acid (1401-55-4), Propane/n-Butane (68476-86-8).

HEALTH	2
FLAMMABILITY	4
REACTIVITY	1
PERSONAL	B

