

Revision Date: 11/19/2020

SAFETY DATA SHEET

Classified in accordance 29 CFR 1910.1200

1. Identification

Product identifier: PENETRATING LUBRICANT WITH PTFE - SW-689

Other means of identification

SDS number: RE1000043598

Recommended restrictions
Recommended use: Lubricant
Restrictions on use: Not known.

Manufacturer Information

Manufacturer

Company Name: Sprayway, Inc.

Address: 1000 INTEGRAM DR.

Pacific, MO 63069

US

Telephone: 1-630-628-3000

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Aspiration Hazard Category 1

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.



Revision Date: 11/19/2020

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face

protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a

POISON CENTER/doctor Do NOT induce vomiting.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
White mineral oil (petroleum)	8042-47-5	20 - <50%
Distillates (petroleum), hydrotreated middle	64742-46-7	20 - <50%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	10 - <20%
Naphtha (petroleum), heavy alkylate	64741-65-7	5 - <10%
Propane	74-98-6	5 - <10%
Butane	106-97-8	5 - <10%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1 - <5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments:

The components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a physician or poison control center immediately. Rinse mouth.

Never give liquid to an unconscious person. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.



Revision Date: 11/19/2020

Personal Protection for Firstaid Responders: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and

emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep

upwind.

Accidental release measures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.



Revision Date: 11/19/2020

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

No data available.

Safe handling advice: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not

pierce or burn, even after use.

Contact avoidance measures: No data available.

Storage

Safe storage conditions: Store locked up. Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 3

Safe packaging materials: No data available.

Storage Temperature: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure L	imit Values	Source
White mineral oil (petroleum) - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
White mineral oil (petroleum) - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated middle - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
•	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated middle - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Ethanol, 2-(2-butoxyethoxy) Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended
Naphtha (petroleum), heavy alkylate	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
,	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended



Revision Date: 11/19/2020

Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), hydrotreated heavy naphthenic	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), hydrotreated heavy naphthenic	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), solvent-refined heavy paraffinic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-refined heavy paraffinic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-refined heavy paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Distillates (petroleum), solvent-refined heavy paraffinic	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Molybdenum sulfide (MoS2) - Respirable fraction as Mo	TWA		3 mg/m3	US. ACGIH Threshold Limit Values, as amended
Molybdenum sulfide (MoS2) - Inhalable fraction as Mo	TWA		10 mg/m3	US. ACGIH Threshold Limit Values, as amended
Molybdenum sulfide (MoS2) - Total dust as Mo	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Di dili di	TWA	400	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as



Revision Date: 11/19/2020

Distillates (petroleum),	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended
solvent-dewaxed heavy paraffinic - Inhalable fraction.		, and the second	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Distillates (petroleum), solvent-refined light paraffinic - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Distillates (petroleum), solvent-refined light paraffinic - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended

Appropriate Engineering

No data available.

Controls

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When

using do not smoke.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor Threshold: No data available.
pH: Estimated 6 - 7
Freezing point: No data available.
Boiling Point: No data available.

Flash Point: -104.44 °C

Evaporation Rate:

Flammability (solid, gas):

Explosive limit - upper (%):

Explosive limit - lower (%):

Estimated 10.9 %(V)

Estimated 0.9 %(V)

Vapor pressure: 2,068 - 3,447 hPa (20 °C)

Vapor density (air=1):No data available.Density:Estimated 0.781 g/cm3Relative density:No data available.Solubility in Water:No data available.



Revision Date: 11/19/2020

Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. **Self Ignition Temperature:** No data available. No data available. **Decomposition Temperature:** Kinematic viscosity: No data available. Dynamic viscosity: No data available. **Explosive properties:** No data available. Oxidizing properties: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Dermal

Product: Not classified for acute toxicity based on available data.



Revision Date: 11/19/2020

Inhalation

Product: ATEmix: 16.12 mg/l Dusts, mists and fumes

Repeated dose toxicity

Product: No data available.

Components:

White mineral oil NOAEL (Rat(Female, Male), Oral, 90 d): >= 20,000 ppm(m) Oral

(petroleum) Experimental result, Key study

Distillates (petroleum), LOAEL (Rat(Female, Male), Inhalation): 24 mg/m3 Inhalation Experimental

hydrotreated middle result, Key study

NOAEL (Rabbit(Female, Male), Dermal): 1,000 mg/kg Dermal Experimental

result, Key study

NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation Ethanol, 2-(2-

Experimental result, Key study butoxyethoxy)-

NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental

result. Kev study

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Propane

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Butane

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

Distillates (petroleum),

NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m3 Inhalation hydrotreated heavy Experimental result, Key study

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): >= 2,000 mg/kg Dermal naphthenic

Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Components:

White mineral oil in vivo (Rabbit): Not irritant

(petroleum)

Distillates (petroleum), in vivo (Rabbit): Not irritant

hydrotreated middle

Ethanol, 2-(2in vivo (Rabbit): Not irritant

butoxyethoxy)-

Distillates (petroleum),

hydrotreated heavy

naphthenic

in vivo (Rabbit): Not irritant

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

White mineral oil (petroleum)

Rabbit, 24 - 72 hrs: Not irritating

Distillates (petroleum), hydrotreated middle

Rabbit, 24 hrs: Not irritating

Rabbit, 24 - 72 hrs: Highly irritating

Ethanol, 2-(2butoxyethoxy)-



Revision Date: 11/19/2020

Distillates (petroleum), hydrotreated heavy naphthenic

Rabbit, 48 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Components:

White mineral oil

Skin sensitization:, in vivo (Guinea pig): Non sensitising

(petroleum)

Distillates (petroleum), hydrotreated middle

Skin sensitization:, in vivo (Guinea pig): Non sensitising

Ethanol, 2-(2butoxyethoxy)- Skin sensitization:, in vivo (Guinea pig): Non sensitising

Distillates (petroleum),

hydrotreated heavy

Skin sensitization:, in vivo (Guinea pig): Non sensitising

naphthenic

Carcinogenicity **Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

No data available. **Product:**

Aspiration Hazard

Product: No data available.

Components:

White mineral oil May be fatal if swallowed and enters airways.

(petroleum)

Naphtha (petroleum), May be fatal if swallowed and enters airways.

heavy alkylate

Other effects: No data available.



Revision Date: 11/19/2020

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

NOAEL (Oncorhynchus mykiss, 96 h): >= 100 mg/l Experimental result, Key White mineral oil

(petroleum) study

LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result, Ethanol, 2-(2-

butoxyethoxy)-Supporting study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Distillates (petroleum),

hydrotreated heavy

naphthenic

LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key

study

Aquatic Invertebrates

Product: No data available.

Components:

White mineral oil (petroleum)

NOAEL (Daphnia magna, 48 h): >= 100 mg/l Experimental result, Key study

Ethanol, 2-(2-LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting

butoxyethoxy)study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Distillates (petroleum), hydrotreated heavy

EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study NOAEL (Daphnia magna, 48 h): >= 10,000 mg/l Experimental result, Key

naphthenic study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Components:

(petroleum)

White mineral oil

NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting

study

Distillates (petroleum), hydrotreated heavy

naphthenic

NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting

study

Aquatic Invertebrates

Product: No data available.

Components:

White mineral oil (petroleum)

NOAEL (Daphnia magna): >= 1,000 mg/l QSAR QSAR, Supporting study



Revision Date: 11/19/2020

Distillates (petroleum), hydrotreated heavy naphthenic NOAEL (Daphnia magna): 10 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Components:

White mineral oil (petroleum)

31 % (28 d) Detected in water. Read-across from supporting substance

(structural analogue or surrogate), Supporting study

Distillates (petroleum), hydrotreated middle

41.96 % Detected in water. Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)-

85 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Distillates (petroleum), hydrotreated heavy naphthenic 31 % (28 d) Detected in water. Read-across based on grouping of

substances (category approach), Supporting study

2 - 4 % (28 d) Detected in water. Experimental result, Supporting study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Components:

White mineral oil (petroleum)
Distillates (petroleum), hydrotreated middle
Ethanol, 2-(2-butoxyethoxy)Naphtha (petroleum), heavy alkylate
Propane
Butane
Distillates (petroleum), hydrotreated heavy naphthenic
No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws

Contaminated Packaging: No data available.



Revision Date: 11/19/2020

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1 Label(s): EmS No.:

Packing Group:

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Ш

Transport Hazard Class(es):

Class: 2.1 Label(s): Packing Group:

Special precautions for user: Not regulated.

Other information

Passenger and cargo aircraft: Allowed. 203 Cargo aircraft only: Allowed, 203

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): EmS No.:

Packing Group:

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

GLYCOL ETHERS

UNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY

RCRA HAZARDOUS WASTE NO. D001

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable aerosol, Serious Eye Damage/Eye Irritation, Aspiration Hazard



Revision Date: 11/19/2020

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Chemical Identity</u> % by weight

Ethanol, $\overline{2-(2-butoxyethoxy)}$ - $\overline{1.0\%}$

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act Chemical Identity

White mineral oil (petroleum)

Distillates (petroleum), hydrotreated middle

Ethanol, 2-(2-butoxyethoxy)-

Naphtha (petroleum), heavy alkylate

Propane

Butane

Distillates (petroleum), hydrotreated heavy naphthenic

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates (petroleum), solvent-refined light paraffinic

US. Pennsylvania RTK - Hazardous Substances Chemical Identity

White mineral oil (petroleum)

Distillates (petroleum), hydrotreated middle

Ethanol, 2-(2-butoxyethoxy)-

Naphtha (petroleum), heavy alkylate

Propane

Butane

Distillates (petroleum), hydrotreated heavy naphthenic

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable



Revision Date: 11/19/2020

Inventory Status:

Australia AICS On or in compliance with the inventory

Canada DSL Inventory List On or in compliance with the inventory

EINECS, ELINCS or NLP Not in compliance with the inventory.

Japan (ENCS) List Not in compliance with the inventory.

China Inv. Existing Chemical Substances

On or in compliance with the inventory

Korea Existing Chemicals Inv. (KECI)

Not in compliance with the inventory.

Canada NDSL Inventory Not in compliance with the inventory.

Philippines PICCS On or in compliance with the inventory

US TSCA Inventory On or in compliance with the inventory

New Zealand Inventory of Chemicals

On or in compliance with the inventory

Japan ISHL Listing Not in compliance with the inventory.

Japan Pharmacopoeia Listing

Not in compliance with the inventory.

Mexico INSQ Not in compliance with the inventory.

Ontario Inventory Not in compliance with the inventory.

Taiwan Chemical Substance Inventory

On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 11/19/2020

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.