



CAMIE-CAMPBELL, INC.
Aerosol and Bulk Industrial Specialty Chemicals



2651 Warrenville Road • Downers Grove, IL 60515
Phone: 800-325-9572 • Fax: 314-968-0741
E-mail: info@camie.com • www.camie.com

CAMIE 556 PRODUCT DATA SHEET

Camie 556 Spray Adhesive

Developed to offer the user a product that is versatile to use on a wide range of substrates. While it works well on wood, foam, fabric and nonwovens, the user will find it bonds well to paper, drywall, masonry, plastic and painted surfaces.

Applications	Works well on: wood, foam, fabric and non-wovens. Bonds: paper, drywall, masonry, plastic and painted surfaces.
Container Size	20 Fluid oz. Container
Product Description	Spray Adhesive
Net Weight	12 Ounces
Cans Per Case	12
Case Dimensions Inches	10 3/4 L x 8 3/16 W x 10 3/16 H
Case Weight	13.3 lbs
Cases Per Pallet	72 Cases
Appearance	White
Odor	Mint When Wet
Solvent System	Heptane Acetone & Methyl Acetate
Propellant	DME Hydrocarbon Blend
Bond Time	20 Seconds to 2 Minutes
Heat Resistance	Max. Service Temperature 130 °F
Solids	26% +/-1%
Spray Pattern	Lace
VOC %	38.6%
VOC Compliant for CA & OTC	Yes
Aerosol Flammability Level	Level 3
Warranty Period	One Year From Date of Shipment



CAMIE 556

In as much as CAMIE-CAMPBELL, INC. has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.